

TITUS®
At the leading edge for complex security missions

KNDS



/ TITUS® AT THE LEADING EDGE FOR HIGH INTENSITY AND COMPLEX SECURITY MISSIONS

TITUS® has been designed to answer an evolutive worldwide demand for complex security missions: from Homeland Security missions to counter terrorism, border monitoring and public security.

Based on a robust architecture TITUS® provides a rugged off road mobility combined with a high payload capability and unique manoeuvrability performances which enables it to operate in confined urban environments while providing an optimized level of protection to the SWAT units.



Platform

- APC dedicated to SWAT units
- Crisis Coordination & Command Post

Homeland security missions

- Law enforcement
- Public Security
- Critical Infrastructure protection
- Anti-terrorism
- Urban Warfare
- Border monitoring

Mobility

- TATRA – T815 chassis
- Turning circle between kerbs adapted to urban environment (13m)
- Significant payload growth potential
- COTS maintenance and reliability
- Obstacle clearance
- Rapid acceleration and efficient breaking



Protection

- EN B7 ballistic side protection, DM-51 grenade protected ground floor
- Mine protection: up to 4a/4b
- IED: up to 150kg

Human integration

- Tactical pivoting seat for front vision and optimised collaborative dialogue with the squad
- Hatches, rear ramp and side doors for easy ingress/egress
- Large interior volume for personnel equipment storage
- Perimeter vision

Public security equipment

- Public address, police sign, siren, penetrating lights, 360 LEDs, search light, height adjustable protection grid, anti-Molotov cocktail protection, NBC, smokegrenade launcher, assault ladder, jammer, photo/video recorder, observation mast, anti-barricade blade, crowd pusher, bull bars.
- On-board remotely controlled UAV and/or UGV

/ TITUS® features and specifications



Weight And Dimensions

- Unladen weight:** 17t
- Operational weight:** 23t
- Maximum gross weight:** 27t
- Width:** 2.55m
- Height:** 2.73 m (roof)
- Length:** 7.77 m
- Ground clearance:** 0.3/0.4/0.5m

Protection

- Standard:**
 - **Ballistic level:** 2 to 4
 - **Mines level:** 3A/3B until 4A/4B
 - **IED blast:** from 50 to 150kg

Higher levels upon request

Mobility

- Engine:** 500HP
- Running gear:** Semi-independent stub axle.
- Tyres:** Michelin 16.R20, SYEGON® CTIS and flat-running system
- Steering:** Steering axle # 1 and 3. Turning circle: 13m

Human Integration

- Crew:** 3+10 or 2+12 depending on configuration
- Interior volume:** 14.4m³
- Storage capacity:** 2.4m³ inside, 1.5m³ outside
- Ramp and openable side doors
- 6 front side windows and roof hatches

Performance

- Range:** 700km
- Maximum speed:** 110km/h
- Slope:** 60%
- Step:** 700mm
- Ground clearance:** 450mm
- Side slope:** 30%
- Fording:** 1.2m without preparation

Outside Vision

- One front windscreen and two side windows (transparent armour)
- One rear ramp window with firing port
- Three side windows on each side in the rear compartment (option)

Liveability

- Air conditioning / heating system (weather conditions A1/C0/C1 optional)
- Air renewal:** 240m³/h
- Full NRBC (as optional)

Energy

- Four AGM 12V – 120Ah batteries
- One alternator delivering 370A





KNDS

KNDS France

13 route de la Minière
78034 Versailles Cedex France
Tél. +33 (1) 30 97 37 37
www.knds.com

Unless otherwise indicated, all products are registered
trademarks of KNDS France.

Property of KNDS. All rights reserved.

K2V-011-EN-06/2024